

MPC7447A Hardware Specification Addendum for the MC7447ATxxnnnnNx Series

This document describes part-number-specific changes to recommended operating conditions and revised electrical specifications, as applicable, from those described in the general *MPC7447A RISC Microprocessor Hardware Specifications*. The MPC7447A is a PowerPC™ microprocessor.

Specifications provided in this document supersede those in the *MPC7447A RISC Microprocessor Hardware Specifications* (Freescale document order number MPC7447AEC), Rev 1 or later, for the part numbers listed in [Table A](#) only. Specifications not addressed herein are unchanged.

Note that headings and table numbers in this document are not consecutively numbered. They are intended to correspond to the heading or table affected in the general hardware specification.

Freescale Part Numbers Affected:

*MC7447ATHX867NB
MC7447ATHX1000NB
MC7447ATHX1167NB*

General Parameters

Part numbers addressed in this document are listed in [Table A](#).

Table A. Part Numbers Addressed by this Data Sheet

Motorola Part Number	Operating Conditions			Significant Differences from Hardware Specification
	CPU Frequency (MHz)	V _{DD}	T _j (°C)	
MC7447ATHX867NB	867	1.1 V ± 50 mV	-40 to 105	Modified core frequency and voltage to reduce power consumption; extended temperature range.
MC7447ATHX1000NB	1000			
MC7447ATHX1167NB	1167			

4 General Parameters

Core power supply 1.1 V ± 50 mV DC (nominal), or
 1.0 V ± 50 mV DC (derated)

5.1 DC Electrical Characteristics

[Table 4](#) provides the recommended operating conditions for the MPC7447A part numbers described herein.

NOTE

[Table 4](#) describes the nominal operating conditions of the device. For information regarding the operation of the device at supported derated core voltage conditions, see [Section 5.3, “Voltage and Frequency Derating.”](#)

Table 4. Recommended Operating Conditions ¹

Characteristic	Symbol	Recommended Value	Unit	Notes
Core supply voltage	V _{DD}	1.1 V ± 50 mV	V	3
PLL supply voltage	AV _{DD}	1.1 V ± 50 mV	V	2, 3

Note:

1. These are the recommended and tested operating conditions. In addition, these devices also support voltage derating; see [Section 5.3, “Voltage and Frequency Derating.”](#) Proper device operation outside of these conditions and those specified in [Section 5.3](#) is not guaranteed.
2. This voltage is the input to the filter discussed in *MPC7447A RISC Microprocessor Hardware Specifications*, Section 9.2, “PLL Power Supply Filtering,” and not necessarily the voltage at the AV_{DD} pin, which may be reduced from V_{DD} by the filter.
3. V_{DD} and AV_{DD} may be reduced in order to reduce power consumption if further maximum core frequency constraints are observed. See [Section 5.3, “Voltage and Frequency Derating,”](#) for specific information.

Table 7 provides the power consumption for the MPC7447A part numbers described herein. For information regarding power consumption when dynamic frequency switching (DFS) is enabled, see the *MPC7447A RISC Microprocessor Hardware Specifications*.

NOTE

The power consumption information in this table applies when the device is operated at the nominal core voltage indicated in Table 4. For power consumption at derated core voltage conditions, see Section 5.3, “Voltage and Frequency Derating.”

Table 7. Power Consumption for MPC7447A

	Processor (CPU) Frequency			Unit	Notes
	867 MHz	1000 MHz	1167 MHz		
Full-Power Mode					
Typical	7.8	8.0	9.2	W	1, 2
Maximum	10.3	11.5	13.0	W	1, 3
Nap Mode					
Typical	1.3	1.3	1.3	W	1, 2
Sleep Mode					
Typical	1.3	1.3	1.3	W	1, 2
Deep Sleep Mode (PLL Disabled)					
Typical	1.2	1.2	1.2	W	1, 2

Notes:

1. These values apply for all valid processor buses. The values do not include I/O supply power (OV_{DD}) or PLL supply power (AV_{DD}). OV_{DD} power is system dependent but is typically < 5% of V_{DD} power. Worst case power consumption for AV_{DD} < 3 mW.
2. Typical power is an average value measured at the nominal recommended V_{DD} (see Table 4) and 65°C while running the Dhrystone 2.1 benchmark and achieving 2.3 Dhrystone MIPs/MHz.
3. Maximum power is the average measured at nominal V_{DD} and maximum operating junction temperature (see Table 4) while running an entirely cache-resident, contrived sequence of instructions which keep all the execution units maximally busy.
4. Doze mode is not a user-definable state; it is an intermediate state between full-power and either nap or sleep mode. As a result, power consumption for this mode is not tested.

5.2 AC Electrical Characteristics

Table 8 provides the clock AC timing specifications for the MPC7447A part numbers described herein.

NOTE

The core frequency information in this table applies when the device is operated at the nominal core voltage indicated in Table 4. For core frequency specifications at derated core voltage conditions, see Section 5.3, “Voltage and Frequency Derating.”

Table 8. Clock AC Timing Specifications

At recommended operating conditions. See Table 4.

Characteristic	Symbol	Maximum Processor Core Frequency						Unit	Notes
		867 MHz		1000 MHz		1167 MHz			
		Min	Max	Min	Max	Min	Max		
Processor frequency	f_{core}	500	867	500	1000	500	1167	MHz	1, 2, 3
VCO frequency	f_{VCO}	1000	1733	1000	2000	1000	2333	MHz	1, 3

Notes:

- Caution:** The SYSCLK frequency and PLL_CFG[0:4] settings must be chosen such that the resulting SYSCLK (bus) frequency, CPU (core) frequency, and PLL (VCO) frequency do not exceed their respective maximum or minimum operating frequencies. Refer to the PLL_CFG[0:4] signal description in *MPC7447A RISC Microprocessor Hardware Specifications*, Section 9.1, “PLL Configuration,” for valid PLL_CFG[0:4] settings.
- Caution:** If dynamic frequency switching (DFS) is enabled, the SYSCLK frequency and PLL_CFG[0:4] settings must be chosen such that the resulting processor frequency is greater than or equal to the minimum core frequency.
- Caution:** These values specify the maximum processor core and VCO frequencies when the device is operated at the nominal core voltage. If operating the device at the derated core voltage, the processor core and VCO frequencies must be reduced. See Section 5.3, “Voltage and Frequency Derating,” for more information.

5.3 Voltage and Frequency Derating

To reduce the power consumption of the device, these devices support voltage and frequency derating whereby the core voltage (V_{DD}) may be reduced if the reduced maximum processor core frequency requirements are observed. The supported derated core voltage, resulting maximum processor core frequency (f_{core}), and power consumption are provided in Table 11. Only those parameters in Table 11 are affected; all other parameter specifications are unaffected.

Table 11. Supported Voltage, Core Frequency, and Power Consumption Derating

Maximum Rated Core Frequency (Device Marking)	Supported Derated Core Voltage (V_{DD})	Maximum Derated Core Frequency (f_{core})	Full-Power Mode Power Consumption	
			Maximum	Typical
867	1.0 V \pm 50mV	667	6.9 W	4.9 W
1000		800	8.0 W	5.6 W
1167		1000	9.4 W	6.6 W

11 Ordering Information

11.1 Part Numbers Addressed by This Specification


Table 17 provides the ordering information for the MPC7447A parts described in this document.

Table 17. Part Marking Nomenclature

MC	7447A	T	xx	nnnn	N	x
Product Code	Part Identifier	Specification Modifier	Package	Processor Frequency	Application Modifier	Revision Level
MC	7447A	T = Extended Temperature Device	HX = HCTE	867 1000 1167	N: 1.1 V ± 50 mV -40 to 105°C	B:1.1: PVR = 8003 0101

11.3 Part Marking

Parts are marked as the example shown in Figure 23.



Notes:

- AWYYYYWW is the test code.
- MMMMMM is the M00 (mask) number.
- YWWWLAZ is the assembly traceability code.

Figure 23. Part Marking for BGA Device

Document Revision History

Table B provides a revision history for this hardware specification addendum.

Table B. Document Revision History

Rev. No.	Date	Substantive Change(s)
1	10/05/2004	Added information on voltage derating, including Table 7 and Table 8; added 1167-MHz speed bin
0	09/27/2004	Initial release

THIS PAGE INTENTIONALLY LEFT BLANK

THIS PAGE INTENTIONALLY LEFT BLANK

How to Reach Us:

USA/Europe/Locations Not Listed:

Freescale Semiconductor
Literature Distribution Center
P.O. Box 5405,
Denver, Colorado 80217
1-480-768-2130
(800) 521-6274

Japan:

Freescale Semiconductor Japan Ltd.
Technical Information Center
3-20-1, Minami-Azabu, Minato-ku
Tokyo 106-8573, Japan
81-3-3440-3569

Asia/Pacific:

Freescale Semiconductor Hong Kong Ltd.
2 Dai King Street
Tai Po Industrial Estate
Tai Po, N.T. Hong Kong
852-26668334

Home Page:

www.freescale.com

Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.

Learn More: For more information about Freescale Semiconductor products, please visit www.freescale.com

Freescale™ and the Freescale logo are trademarks of Freescale Semiconductor, Inc. The described product is a PowerPC microprocessor. The PowerPC name is a trademark of IBM Corp. and used under license. All other product or service names are the property of their respective owners.

© Freescale Semiconductor, Inc. 2004.

MPC7447AECS02AD
Rev. 1
10/2004