

ARN

Android Release Notes

Rev. automotive-12.0.0_2.1.0 —
1 September 2022

Release notes

Document information

Information	Content
Keywords	Android, i.MX, automotive-12.0.0_2.1.0
Abstract	The i.MX Android automotive-12.0.0_1.1.0 release is an Android Automotive GA (RFP) release on NXP's i.MX 8QuadXPlus/8QuadMax MEK board and platform, which is based on Android 12.



1 Release Description

The i.MX Android automotive-12.0.0_2.1.0 release is an Android Automotive GA (RFP) release on NXP's i.MX 8QuadXPlus/8QuadMax MEK board and platform, which is based on Android 12. It supports the device type In-vehicle infotainment defined in <https://source.android.com/devices/automotive/>.

i.MX Android automotive-12.0.0_2.1.0 release includes all necessary code, documents, and tools to assist users in building and running Android Automotive on the i.MX 8QuadXPlus/8QuadMax MEK board from scratch. Pre-built images are also included for a quick trial on the following platforms:

- i.MX 8QuadXPlus/8QuadMax MEK Board and Platform

This release includes all porting and enhancements based on the Android open source code.

Most of the deliveries in this release are provided in source code with the exception of some proprietary modules/libraries from third parties.

2 Supported Hardware SoC/Boards

The supported hardware system-on-chip (SoCs)/boards are listed as follows:

- i.MX 8QuadMax (Silicon Revision B0) MEK Board and Platform
- i.MX 8QuadXPlus (Silicon Revision B0, C0) MEK Board and Platform

3 Release Package Contents

The automotive-12.0.0_2.1.0 release package includes the following software and documents.

Table 1. Release package contents

i.MX Android proprietary source code package	<ul style="list-style-type: none"> • <code>imx-automotive-12.0.0_2.1.0.tar.gz</code>: i.MX Android Automotive proprietary source code package to enable Android Automotive on i.MX boards. For example, Hardware Abstraction Layer implementation, and hardware codec acceleration.
Documents	<p>The following documents are included in <code>android_automotive-12.0.0_2.1.0_docs.zip</code>:</p> <ul style="list-style-type: none"> • <i>Android Quick Start Guide (AQSUG)</i>: A document that explains how to run Android Automotive on an i.MX board using prebuilt images. • <i>Android User's Guide (AUG)</i>: A document describing procedures for configuring and building this release package. • <i>Android Release Notes (ARN)</i>: A document that introduces key updates and known issues in this release. • <i>i.MX Android Extended Codec Release Notes (IMXACRN)</i>: A document that provides the extended codec information. • <i>i.MX Android Security User's Guide (ASUG)</i>: A document that describes how to do customization work on security features supported by i.MX Android software. • <i>i.MX TensorFlow Lite on Android User's Guide (IMXTFLUG)</i>: A document that describes the TensorFlow Lite on Android platform. • <i>i.MX Graphics User's Guide (IMXGRAPHICUG)</i>: A document that describes GPU 2D API, Tools, Memory, and Application programming guidelines.

Table 1. Release package contents...continued

Prebuilt images	<p>You can test Android Automotive with a prebuilt image on i.MX reference board before building any code:</p> <ul style="list-style-type: none"> <code>automotive-12.0.0_2.1.0_image_8qmek_car.tar.gz</code>: Prebuilt images with NXP extended features with the EVS function enabled in the Cortex-M4 CPU core for the i.MX 8QuadMax/8QuadXPlus MEK board. The extended features include more multimedia format support. <code>automotive-12.0.0_2.1.0_image_8qmek_car2.tar.gz</code>: Prebuilt images with NXP extended features without EVS function enabled in the Cortex-M4 CPU core for the i.MX 8QuadMax/8QuadXPlus MEK board. <p>All prebuilt images are in a separate package. See the <i>Android Quick Start Guide (AQSUG)</i> and <i>Android User's Guide (AUG)</i> to choose the appropriate image.</p>
-----------------	---

4 Features

This section describes features in this package.

Table 2. Features

Feature	i.MX 8QuadXPlus/ 8QuadMax MEK	Remarks
Google Android 12 release	Y	Based on android-12.0.0_r28 release.
Linux 5.15.41 kernel (merged with the AOSP kernel)	Y	Based on Linux OS BSP L5.15.32 GA release.
U-Boot	Y	v2022.04
Trusty OS	Y	-
Graphics-HW	Y	VeriSilicon GC7000L GPU for i.MX 8QuadXPlus, GC7000XSVX GPU for i.MX 8QuadMax with 6.4.3.p4 driver
Graphics-HW 3D acceleration	Y	OpenGL ES 1.1/2.0/3.1 through GC7000L for i.MX 8QuadXPlus, OpenGL ES 1.1/2.0/3.1/3.2 through GC7000XSVX for i.MX 8QuadMax.
Graphics-HW accelerated UI surface composition	Y	OpenGL ES 3.1 through GC7000L for i.MX 8QuadXPlus, OpenGL ES 3.2 through GC7000XSVX for i.MX 8QuadMax.
SCFW	Y	Version 1.13.0
SECO firmware	Y	Version 3.8.5 for i.MX 8QuadMax B0 and i.MX 8QuadXPlus B0, Version 3.8.6 for i.MX 8QuadXPlus C0.
Boot source	eMMC	-
Splash Screen	Y	Supports USB mouse.
UI (input)	Y	-
UI (display)	HDMI display	Supports LVDS-to-HDMI display.
UI (brightness control)	N	-

Table 2. Features...continued

Feature	i.MX 8QuadXPlus/ 8QuadMax MEK	Remarks
Storage - External Media	Y	-
Connectivity - Ethernet	Y	Atheros AR8031
Connectivity - Bluetooth wireless technology	Y	NXP 88W8997. Profiles: A2DP Sink, AVRCP, BLE Host, HFP, PBAPClient, MAPMCE, PAN, MAPMCE, PAN, HID Device.
Connectivity - Wi-Fi	Y	NXP 88W8997. Features: STA mode, AP mode, AP/STA Concurrency.
Connectivity - USB Tethering	Y	Supports Wi-Fi as upstream.
Power - CPU Freq	Y	-
Power - Bus Freq	Y	-
Media - Music Play	Y	SAI+WM8960 (for system sounds) ESAI+CS42888 (no support for multichannel). SOF+ESAI+CS42888 (with special dtbo image)
Media - HDMI audio output	N	-
Misc - ADB over USB	Y	-
Misc - Fastboot utility	Y	-
Misc - SW update and factory reset	Y	-
File-based Encryption	Y	-
webGL	Y	-
Vulkan	Y	-
USB TYPEC PD	Y	-
OTA for A/B	Y	-
TEE backed Keymaster HAL	Y	This is based on i.MX Trusty OS TEE firmware.
TEE backed AVB	Y	This is based on i.MX Trusty OS TEE firmware and secure storage of eMMC chip. In this release, the RPMB part needs to be initialized manually.
Media rearview camera	Y	MAX9286 camera.
Car Audio Policy	Y	Alarm, notification, and system sounds are played from the audio jack on the CPU board. Other sounds such as music are played from the extended audio board.

5 Multimedia Codecs

For multimedia codecs and features, see the *i.MX Android Extended Codec Release Notes* (IMXACRN).

6 Change Log

Compared to the automotive-12.0.0_1.1.0 release, android-12.0.0_2.1.0 has the following major changes:

- Upgraded the Android code base from android-12.0.0_r26 to android-12.0.0_r28.
- Added support of Sound Open Firmware (SOF) running on DSP. With SOF enabled, multimedia playback is managed by DSP.
- Fixed crash of Local Media Player in case when Genres menu is accessed by users.
- Changed audio playback period size from 768 to 384 samples to pass Android CTS media tests.
- Fixed U-Boot Makefile to not use hardcoded CMake path.
- NCM USB gadget is used instead of RNDIS for USB Ethernet tethering.

7 Known Issues and Limitations

The known issues about the hardware and hardware rework instructions are not included in this document. Read all hardware-related reference materials and ensure the necessary hardware modifications have been made before using the software.

Table 3. Known issues and limitations

Issue description	Remarks
The Google USB driver must be installed multiple times for the MTP, PTP, MTP&ADB, PTP&ADB, and ADB function settings.	Some Windows XP environments may display MTP and PTP windows even with only PTP enabled in the device.
For i.MX 8QuadXPlus silicon revision B0 chip, it fails to boot from some types of eMMC.	<p>In the default settings, the UUU script burns the boot image into eMMC Boot Partition with 32KB offset. Although it works properly on the MEK board, it fails to read the boot image on some types of eMMC.</p> <p>There are two possible solutions:</p> <ul style="list-style-type: none">• Download <code>flash.bin</code> in the eMMC Boot Partition + 0KB offset + eMMC fastboot enabled in fuse.• Download <code>flash.bin</code> in the eMMC User Partition + 32KB offset (eMMC fastboot can be either enabled or disabled in fuse). <p>For more information, see https://community.nxp.com/docs/DOC-342877.</p>
The “carwatchdogd” service can cause shutdown of the application, which requires more system time.	This is a feature of Android automotive OS.

Table 3. Known issues and limitations...continued

Issue description	Remarks
Support of surround view application (sv_app) is experimental only and not fully tested.	Surround view application will be improved in a future release.
The board stays offline (no ADB or fastboot connection) during reboot stress test. The issue is reproducible after 1028 iteration (around 18 hours).	This issue will be fixed in next release.
Camera freezes in 10 minutes.	This issue will be fixed in next release.

8 Revision History

Table 4. Revision history

Revision number	Date	Substantive changes
O8.1.0_1.1.0_AUTO-EAR	02/2018	Initial release
O8.1.0_1.1.0_AUTO-beta	05/2018	i.MX 8QuadXPlus/8QuadMax Beta release
P9.0.0_1.0.2-AUTO-alpha	11/2018	i.MX 8QuadXPlus/8QuadMax Automotive Alpha release
P9.0.0_1.0.2-AUTO-beta	01/2019	i.MX 8QuadXPlus/8QuadMax Automotive Beta release
P9.0.0_2.1.0-AUTO-ga	04/2019	i.MX 8QuadXPlus/8QuadMax Automotive GA release
P9.0.0_2.1.0-AUTO-ga	08/2019	Updated the location of the SCFW porting kit
automotive-10.0.0_1.1.0	03/2020	i.MX 8QuadXPlus/8QuadMax MEK (Silicon Revision B0) GA release
android-10.0.0_2.2.0-AUTO	06/2020	i.MX 8QuadXPlus/8QuadMax MEK GA release
android-10.0.0_2.4.0	07/2020	i.MX 8QuadMax MEK GA release
android-11.0.0_1.1.0-AUTO	01/2021	i.MX 8QuadXPlus/8QuadMax MEK GA release
automotive-11.0.0_2.1.0	11/2021	Integrated the android-11.0.0_r36 version and upgraded the kernel to v5.10.35
automotive-11.0.0_2.3.0	12/2021	Integrated the android-11.0.0_r40 version and upgraded the kernel to v5.10.52
automotive-11.0.0_2.5.0	03/2022	Integrated the android-11.0.0_r46 version and upgraded the kernel to v5.10.72
automotive-12.0.0_1.1.0	06/2022	Integrated the android-12.0.0_r26 version
automotive-12.0.0_2.1.0	09/2022	Integrated the android-12.0.0_r28 version and upgraded the kernel to v5.15.41

9 Legal information

9.1 Definitions

Draft — A draft status on a document indicates that the content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included in a draft version of a document and shall have no liability for the consequences of use of such information.

9.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification. Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Suitability for use in non-automotive qualified products — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

Translations — A non-English (translated) version of a document, including the legal information in that document, is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Security — Customer understands that all NXP products may be subject to unidentified vulnerabilities or may support established security standards or specifications with known limitations. Customer is responsible for the design and operation of its applications and products throughout their lifecycles to reduce the effect of these vulnerabilities on customer's applications and products. Customer's responsibility also extends to other open and/or proprietary technologies supported by NXP products for use in customer's applications. NXP accepts no liability for any vulnerability. Customer should regularly check security updates from NXP and follow up appropriately. Customer shall select products with security features that best meet rules, regulations, and standards of the intended application and make the ultimate design decisions regarding its products and is solely responsible for compliance with all legal, regulatory, and security related requirements concerning its products, regardless of any information or support that may be provided by NXP.

NXP has a Product Security Incident Response Team (PSIRT) (reachable at PSIRT@nxp.com) that manages the investigation, reporting, and solution release to security vulnerabilities of NXP products.

9.3 Trademarks

Notice: All referenced brands, product names, service names, and trademarks are the property of their respective owners.

NXP — wordmark and logo are trademarks of NXP B.V.

Contents

1 Release Description2

2 Supported Hardware SoC/Boards 2

3 Release Package Contents 2

4 Features 3

5 Multimedia Codecs 5

6 Change Log 5

7 Known Issues and Limitations 5

8 Revision History6

9 Legal information 7

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.