



CodeWarrior Development Studio

for ColdFire® Architectures V7.2

Quick Start





CodeWarrior[™] Development Studio for ColdFire® Architectures V7.2 Quick Start

Hardware	1 GHz Pentium [®] compatible processor, 1 GB RAM, CD/DVD-ROM drive, USB port
Operating System	Microsoft [®] Windows [®] XP, or Windows Vista™ Operating Systems
Disk Space	2 GB total, 400 MB on Windows system disk

This Quick Start explains how to install the CodeWarrior Development Studio for ColdFire Architectures V7.2, activate licenses for Basic, Standard, and Professional CodeWarrior Suites, then create, build, and run a sample project using the ColdFire simulator.

NOTE In this document, numbered steps are for advanced users. Lettered steps are expanded descriptions.

Section A: Installing Software

- **NOTE** The Special Edition License is automatically installed with your product. This license allows you to develop projects with up to 128K of C code for the ColdFire V2, V3, and V4.
- 1. Install CodeWarrior software
 - a. Insert CodeWarrior Development Studio for ColdFire Architectures CD or the DVD included with your kit into the CD/DVD-ROM drive — the welcome screen appears (if Auto Install is disabled, run program Setup.exe in the Setup directory of CD).

- **NOTE** The CodeWarrior software may be part of a DVD included with your kit. In this case, click **Install CodeWarrior Development Studio for ColdFire Architectures**, follow the on-screen instructions, and skip to step "Check for updates".
 - b. Click Launch the Installer the install wizard opens.
 - c. Click the Next button the License Agreement screen appears.
 - d. Select the I accept the terms in the license agreement option button.
 - Continue clicking the Next buttons to step through the wizard screens, accepting default settings — the Ready to Install the Program screen appears.
 - f. Click the **Install** button at the end of the installation, a screen appears announcing installation is complete.
 - g. Select the Yes, check for program updates (Recommended) after setup complete checkbox to check for updates.
 - h. Click the Finish button the CodeWarrior Updater dialog box opens.
- 2. Check for updates

NOTE If the updater already has internet connection settings, you may proceed directly to sub-step f.

- a. Click the **Settings** button inside the **CodeWarrior Updater** dialog box the **CodeWarrior Updater Settings** dialog box appears.
- b. Click the **Settings** button the **Connections** page of the **Internet Properties** dialog box appears.
- c. Modify settings, as appropriate, to successfully connect to the Internet.
- d. Click the **OK** button the Internet Properties dialog box closes.
- e. Select an item in the **Update Check Scheduling** list box and click the **OK** button; or click the **Cancel** button.
- f. In the CodeWarrior Updater dialog box, click the Next button.
- g. If necessary, enter username and password.
- h. If updates are available, follow on-screen instructions to download updates to your computer.

NOTE If no updates are found, the software application displays an appropriate message.

- i. Click the **Finish** button the installation completes and the **CodeWarrior Updater** dialog box closes.
- NOTE For licensing and activation of your CodeWarrior Development Studio for ColdFire® Architectures V7.2, refer to the *CodeWarrior Development Suite Quick Start*. Save the license file, license.dat, to the installation root folder. The default location is C:\Program Files\Freescale\CodeWarrior for ColdFire V7.2
- **NOTE** Special Edition: The Special Edition license is automatically installed with your product and you do not need to register it. This license allows you to develop projects with unlimited assembly code, up to 128KB of C Code.
- **NOTE Evaluation Edition**: The Evaluation license is automatically installed with your product and you do not need to register it. This license allows you to develop projects as Professional Edition within the 30-day evaluation period. After 30 days, the license works as Special Edition license (free permanent, but feature limited) which supports up to 128KB of C Code.

Section B: Creating, Building, and Running a Project

- 1. Create new project
 - Select Start > Programs > Freescale CodeWarrior > CodeWarrior for ColdFire V7.2 > CodeWarrior IDE from the task bar— IDE starts; the CodeWarrior Startup dialog box appears.

Startup Dialog Box

Startup	
101010	Create New Project
2 margin	Load Example Project
anothere a	Load Previous Project
	Start Using CodeWarrior
<i>Freescale</i>	🔽 Display on Startup

- b. Click the Create New Project button the Device and Connection page appears.
- c. Select ColdFire Evaluation Boards > ColdFire V2 > M52259EVB (or the device of your choice).

ColdFire New Project		\mathbf{X}
Wizard Map Wizard Map Device and Connection Project Parameters Add Additional Files Processor Expert	Select the derivative or board you would like to use: M5208EV8 M5208EV8 M5208EV8 M5211EVM M52211EV8 M52211EV8 M52212UBMO M52222UBMO M52235EV8 M52235EV8 M52235EV8 M52235EV8 M52235EV8 M52235EV8 M52235EV8 M52235EV8	to Péc USB BDM Multilink.
		Einish Cancel

Device and Connection Page

- d. Select Instruction Set Simulation.
- e. Click the Next button the Project Parameters page appears.
- f. Select C, C++, or both.
- g. Enter a project name in the **Project name** text box. The software automatically creates a folder with the same name in the default location, or click **Set** to browse and select an alternate location for your project.

Project Parameters Page

ColdFire New Project		
Wizard Map Device and Connection Project Parameters Add Additional Files Processor Expert C/C++ Options	Please choose the set of languages to be selections. C C C C++ C language support will be included in the project	Project name: [MyProject]mop Location: [D-Profiles\B17009\My Documents\MyProject Set
	< <u>B</u> ack	<u>N</u> ext > <u>F</u> inish Cancel

h. Click Next — the Add Additional Files page appears.

Add Additional Files Page

ColdFire New Project		×
Wizard Map	Add existing files to the project	Dev(e) 51e
Device and Connection Project Parameters	B-G My Documents B-G My Computer B17009 on B1700	Add Project Hiles
Add Additional Files Processor Expert	Aysembler_images Assembler_images Assembler_images	Remove
C/C++ Options	Com. freescale. doc. core. cheatsf Com. freescale. doc. sa. cheatsf Com. freescale. doc. sa. cheatsh Com. freescale. doc. starcore. che Com. freescale. docs. order	 ✓ Copy files to project ✓ Create main.c/main.asm file
	Select files to be added to the new project and p To copy the added files to the project folder, sele To have the wizard generate default main.c and	ress "Add" ct "Copy Files to Project" or main.asm files, select "Create
	< <u>B</u> ack	Next > Enish Cancel

i. Click Next — the Processor Expert page appears.

Processor Expert Page

ColdFire New Project	
Wizard Map Device and Connection	Rapid Application Development Options:
Project Parameters Add Additional Files	C None C Device Initialization
Processor Expert C/C++ Options	C Processor Expert
	No code is generated, it is necessary to write device nitialization code manually. Project contains startup code only.
	Help < Back Next > Enish Cancel

j. Click Next — the C/C++ Options page appears.

C/C++ Options Page



- click Finish the software creates your project according to your specifications.
- 2. Build and run project
 - a. From the main menu bar, select **Project > Make** IDE updates the files and the links code into the application.
 - From the main menu bar, select **Project > Debug** IDE builds (assembles, compiles, and links) project; the debug window appears.

Debug Window (MyProject.mcp)

M53015EVB_CONSOLE_EXTERNA	L_R	AM.elf (Thread OxC))		
💺 🗏 🛪 🖬 🔂 🕁 🖬	¥				
Stack	Ð	Variables: Live	Value	Location	Ð
_startup	^	No local variables			^
• man	-				-
▼ IB Source: D:\Profiles\P17009\Mu Desure	antal	MuDraianthan maan main			
/*	IGHLS V	MyProject (sources (main	1.0		
* main implementation: use	this	sample to creat	e your own	application	
*					
/ #include "support_common.h /* include peripheral declarations and more ' #if (CONSOLE IO_SUPPORT EVANLE_UART_SUPPORT) /* Standard IO is only possible if Console or UART support is enabled. *. #include <stdio.h></stdio.h>					
int main(void)					
<pre>- + (int counter = 0; #if (CONSOLE_IO_SUPPORT ENABLE_UART_SUPPORT) printf("Hello World in C from MCF53015 derivative on M53015EVB board' #endif</pre>			urd'		
O. Line 12 Col 1 Source ► ◀					

- c. From the main menu bar, select **Project > Run** debugger downloads program to the simulator and runs program; a new console window shows program *Hello World* output.
- d. From the main menu bar, select **Debug > Kill** the debug session ends; you may close all open windows.

Congratulations!

You just used CodeWarrior software to create, build, and run a simple program.

Freescale[™] and the Freescale logo are trademarks of Freescale Semiconductor, Inc. CodeWarrior is a trademark or registered trademark of Freescale Semiconductor, Inc. in the United States and/or other countries. PROCESSOR EXPERT and EMBEDDED BEANS are trademarks of Freescale Semiconductor, Inc. All other product or service names are the property of their respective owners.

Copyright © 2008–2009 Freescale Semiconductor, Inc. All rights reserved.

Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals", must be validated for each customer application by customer's technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life. or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application. Buver shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.

How to Contact Us

Corporate Headquarters	Freescale Semiconductor, Inc. 6501 William Cannon Drive West Austin, Texas 78735 U.S.A.
World Wide Web	http://www.freescale.com/codewarrior
Technical Support	http://www.freescale.com/support



Revised: 20 November 09





