

Android™ Release Notes

Contents

1 Release Description

The i.MX Android™ 08.1.0_2.0.1-ga release is a GA (RFP) release for the Android 8.1 Oreo (O) platform on the i.MX 8QuadMax MEK board applications processors.

i.MX Android 08.1.0_2.0.1-ga release includes all necessary code, documents, and tools to assist users in building and running the Android 8.1 platform on the i.MX 8QuadMax MEK board from scratch. Pre-built images are also included for a quick trial on the following platform:

- i.MX 8QuadMax MEK B0 Board and Platform

This release includes all porting and enhancements based on the Android open source code.

Most of the deliveries in this release are provided in source code with the exception of some proprietary modules/libraries from third parties.

2 Supported Hardware SoC/Boards

The supported hardware system-on-chip (SoCs)/boards are listed as follows:

- i.MX 8QuadMax MEK B0 Board and Platform

1	Release Description.....	1
2	Supported Hardware SoC/Boards.....	1
3	Release Package Contents.....	2
4	Features	2
5	Multimedia Codecs.....	4
6	Extended Feature Packages.....	4
7	Change Log.....	4
8	Known Issues and Limitations.....	4
9	Revision History.....	5



3 Release Package Contents

The O8.1.0_2.0.1-ga release package includes the following software and documents.

Table 1. Release package contents

i.MX Android proprietary source code package	<ul style="list-style-type: none"> imx-o8.1.0_2.0.1-ga.zip: i.MX Android proprietary source code package to enable the Android platform on i.MX boards.
Documents	<p>The following documents are included in android_o8.1.0_2.0.1-ga_docs.zip:</p> <ul style="list-style-type: none"> <i>Android™ Quick Start Guide</i> (AQSUG): A document that explains how to run the Android platform on an i.MX board using prebuilt images. <i>Android™ User's Guide</i> (AUG): A document describing procedures for configuring and building this release package. <i>Android™ Release Notes</i> (ARN): A document that introduces key updates and known issues in this release. <i>i.MX Android™ Extended Codec Release Notes</i> (IMXACRN): A document that provides the extended codec information. <i>i.MX Graphics User's Guide</i> (IMXGRAPHICUG): A document that describes GPU 2D API, Tools, Memory, and Application programming guidelines.
Prebuilt images	<p>You can test the Android platform with a prebuilt image on an i.MX reference board before building any code:</p> <ul style="list-style-type: none"> android_o8.1.0_2.0.1-ga_image_8qmek.tar.gz: Prebuilt images with NXP extended features for the i.MX 8QuadMax MEK board. The extended features include additional multimedia format support. <p>All prebuilt images are in a separate package. See the <i>Android™ Quick Start Guide</i> (AQSUG) and <i>Android™ User's Guide</i> (AUG) to choose the appropriate image.</p>

NOTE

VivanteVTK tool is no longer provided in the Android release package. It is available on <https://www.nxp.com/imx6tools> (for example: Tools -> Vivante VTK -> VivanteVTK-v6.2.4.p4.1.7.8).

4 Features

This section contains features in this package.

Table 2. Features

Feature	i.MX 8QuadMax MEK	Remarks
Google Oreo 8.1 release	Y	Based on android-8.1.0_r60 release.
Linux 4.14.98 kernel (merged with AOSP kernel)	Y	Based on Linux® OS BSP L4.14.98-2.0.0_ga release.
U-Boot	Y	v2018.03.
Graphic-HW	Y	VeriSilicon GC7000XSVX GPU with 6.2.4.p4 driver.
Graphic-HW 3D acceleration	Y	OpenGL ES 1.1/2.0/3.1/3.2 through GC7000XSVX.

Table continues on the next page...

Table 2. Features (continued)

Feature	i.MX 8QuadMax MEK	Remarks
Graphic-HW accelerated UI surface composition	Y	OpenGL ES 3.2 through GC7000XSVX.
Boot source	SD/eMMC	-
Splash Screen for LVDS	Y	-
UI (input)	Y	-
UI (display)	HDMI/MIPI panel display	LVDS-to-HDMI/MIPI-to-HDMI/MIPI panel display and physical HDMI display.
UI (dual display, HDMI+HDMI, UI mirror displayed on second device)	Y	Supports dual LVDS-to-HDMI display.
UI (brightness control)	N	-
Storage - External Media	Y	The USB 2.0 port supports udisk, but the USB 3.0 port does not support udisk.
Connectivity - Ethernet	Y	-
Connectivity - Bluetooth® wireless technology	Y	Qualcomm QCA6174A. Profiles: A2DP Source, AVRCP, BLE Host, HSP, HID Host, HID Device, PAN, and OPP.
Connectivity - Wi-Fi	Y	Qualcomm QCA6174A. Features: AP mode, STA mode, and Wi-Fi Direct.
Connectivity - USB Tethering	Y	Supports Wi-Fi and Ethernet as upstream
Power - CPU Freq	Y	-
Power - Bus Freq	Y	-
Media - Music Play	Y	WM8960+CS42888+HDMI
Media - Sound Record	Y	ESAI+CS42888
Media - Video Play	Y	-
Media - Camera	Y	OV5640MIPI
Media - TVIN	N/A	PAL/NTSC
Media - Dual Camera	Y	Dual OV5640MIPI.
Media - Camcorder	Y	-
Media - USB Camera	N	-
Media - USB Mic	Y	-
Media - HDMI audio output	Y	Only i.MX 8QuadMax supports HDMI audio output.
Misc - ADB over USB	Y	-
Misc - Fastboot utility	Y	-
Misc - SW update and factory reset	Y	-
Sensor - Magnetometer	Y	FXOS8700
Sensor - Accelerometer	Y	FXOS8700
Sensor - Gyroscope	Y	FXAS2100
Sensor - Light	Y	ISL29023
Sensor - Pressure	Y	MPL3115
Sensor - Temperature	Y	MPL3115

Table continues on the next page...

Table 2. Features (continued)

Feature	i.MX 8QuadMax MEK	Remarks
File Based Encryption	Y	-
USB Accessory	Y	Google AOA v2.0
Ethernet APK	Y	-
webGL	Y	-
OTA for A/B	Y	-
Vulkan	Y	-
USB TYPEC PD	Y	-
DM verity	Y	-

5 Multimedia Codecs

For multimedia codecs and features, see Section 5 in the [Android 8.1 Compatibility Definition Document\(CDD\)](#).

6 Extended Feature Packages

The release extends the default AOSP Android version with the following features. For more information about the features below, contact "L2manager-android@nxp.com". For detailed extended and additional features, see *i.MX Android™ Extended Codec Release Notes* (IMXACRN).

7 Change Log

Compared to the O8.1.0_2.0.0-ga release, this release has the following major changes:

- Updated the SCFW version to support 1.7v PMIC for new i.MX 8QuadMax chips.

8 Known Issues and Limitations

The known issues about the hardware and hardware rework instructions are not included in this document. Read all hardware-related reference material and ensure the necessary hardware modifications have been made before using the software.

Table 3. Known issues and limitations

Issue description	Remarks
The Google USB driver must be installed multiple times for the MTP, PTP, MTP&ADB, PTP&ADB, and ADB function settings.	Some Windows XP environments may display MTP and PTP windows even with only PTP enabled in the device.

Table continues on the next page...

Table 3. Known issues and limitations (continued)

Issue description	Remarks
U-Boot will hang when erasing Kingston's SD card.	U-Boot will hang when sending the erasing command on some Kingston SD cards.
The display is sometimes black on the i.MX 8QuadMax MEK board.	<p>The display is sometime black with the following log on the i.MX 8QuadMax MEK board.</p> <pre>imx-dpu-crtc imx-dpu-crtc.4: flush - wait for content shdld done timeout.</pre> <p>It will be fixed in next release.</p>
Video cannot be played any more after certain HTML5 H.264 or VP8 video playback on i.MX 8QuadMax MEK and i.MX 8QuadXPlux MEK boards.	It will be fixed in next release.

9 Revision History

Table 4. Revision history

Revision number	Date	Substantive changes
O8.0.0_1.2.0_8QXP-EAR	12/2017	Initial release
O8.1.0_1.2.0_8QXP-PRC	03/2018	i.MX 8QuadXPlus PRC/Beta release
O8.1.0_1.2.0_8QXP-beta2	08/2018	i.MX 8QuadXPlus Beta2 release
O8.1.0_2.0.0-beta	01/2019	i.MX 8QuadXPlus/8QuadMax Beta release
O8.1.0_2.0.0-ga	04/2019	i.MX 8QuadXPlus/8QuadMax GA release
O8.1.0_2.0.1ga	06/2019	i.MX 8QuadMax GA release

How to Reach Us:**Home Page:**nxp.com**Web Support:**nxp.com/support

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document. NXP reserves the right to make changes without further notice to any products herein.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: nxp.com/SalesTermsandConditions.

While NXP has implemented advanced security features, all products may be subject to unidentified vulnerabilities. Customers are responsible for the design and operation of their applications and products to reduce the effect of these vulnerabilities on customer's applications and products, and NXP accepts no liability for any vulnerability that is discovered. Customers should implement appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP, the NXP logo, NXP SECURE CONNECTIONS FOR A SMARTER WORLD, COOLFLUX, EMBRACE, GREENCHIP, HITAG, I2C BUS, ICODE, JCOP, LIFE VIBES, MIFARE, MIFARE CLASSIC, MIFARE DESFire, MIFARE PLUS, MIFARE FLEX, MANTIS, MIFARE ULTRALIGHT, MIFARE4MOBILE, MIGLO, NTAG, ROADLINK, SMARTLX, SMARTMX, STARPLUG, TOPFET, TRENCHMOS, UCODE, Freescale, the Freescale logo, AltiVec, C-5, CodeTEST, CodeWarrior, ColdFire, ColdFire+, C-Ware, the Energy Efficient Solutions logo, Kinetis, Layerscape, MagniV, mobileGT, PEG, PowerQUICC, Processor Expert, QorIQ, QorIQ Qonverge, Ready Play, SafeAssure, the SafeAssure logo, StarCore, Symphony, VortiQa, Vybrid, Airfast, BeeKit, BeeStack, CoreNet, Flexis, MXC, Platform in a Package, QUICC Engine, SMARTMOS, Tower, TurboLink, and UMEMS are trademarks of NXP B.V. All other product or service names are the property of their respective owners. AMBA, Arm, Arm7, Arm7TDMI, Arm9, Arm11, Artisan, big.LITTLE, Cordio, CoreLink, CoreSight, Cortex, DesignStart, DynamIQ, Jazelle, Keil, Mali, Mbed, Mbed Enabled, NEON, POP, RealView, SecurCore, Socrates, Thumb, TrustZone, ULINK, ULINK2, ULINK-ME, ULINK-PLUS, ULINKpro, μ Vision, Versatile are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org.

© 2019 NXP B.V.

Document Number ARN
Revision 08.1.0_2.0.1-ga, 06/2019

