



Paragraph
Number

TABLE OF CONTENTS

Page
Number

Section 1 INTRODUCTION

Section 2 NOMENCLATURE

2.1 Symbols and Operators	2-1
2.2 CPU32 Registers	2-2
2.3 Pin and Signal Mnemonics	2-2
2.4 Register Mnemonics	2-4
2.5 Conventions	2-7

Section 3 OVERVIEW

3.1 MCU Features	3-1
3.2 Intermodule Bus	3-3
3.3 System Block Diagram and Pin Assignment Diagrams	3-3
3.4 Pin Descriptions	3-6
3.5 Signal Descriptions	3-8
3.6 Internal Register Map	3-12
3.7 Address Space Maps	3-13

Section 4 CENTRAL PROCESSOR UNIT

4.1 General	4-1
4.2 CPU32 Registers	4-2
4.2.1 Data Registers	4-4
4.2.2 Address Registers	4-5
4.2.3 Program Counter	4-6
4.2.4 Control Registers	4-6
4.2.4.1 Status Register	4-6
4.2.4.2 Alternate Function Code Registers	4-7
4.2.5 Vector Base Register (VBR)	4-7
4.3 Memory Organization	4-7
4.4 Virtual Memory	4-9
4.5 Addressing Modes	4-9
4.6 Processing States	4-9
4.7 Privilege Levels	4-10
4.8 Instructions	4-10
4.8.1 M68000 Family Compatibility	4-14
4.8.2 Special Control Instructions	4-15
4.8.2.1 Low-Power Stop (LPSTOP)	4-15

Paragraph Number	Page Number
4.8.2.2 Table Lookup and Interpolate (TBL)	4-15
4.8.2.3 Loop Mode Instruction Execution	4-15
4.9 Exception Processing	4-16
4.9.1 Exception Vectors	4-16
4.9.2 Types of Exceptions	4-17
4.9.3 Exception Processing Sequence	4-18
4.10 Development Support	4-18
4.10.1 M68000 Family Development Support	4-19
4.10.2 Background Debug Mode	4-19
4.10.3 Enabling BDM	4-20
4.10.4 BDM Sources	4-20
4.10.4.1 External $\overline{\text{BKPT}}$ Signal	4-21
4.10.4.2 BGND Instruction	4-21
4.10.4.3 Double Bus Fault	4-21
4.10.4.4 Peripheral Breakpoints	4-21
4.10.5 Entering BDM	4-21
4.10.6 BDM Commands	4-22
4.10.7 Background Mode Registers	4-23
4.10.7.1 Fault Address Register (FAR)	4-23
4.10.7.2 Return Program Counter (RPC)	4-23
4.10.7.3 Current Instruction Program Counter (PCC)	4-24
4.10.8 Returning from BDM	4-24
4.10.9 Serial Interface	4-24
4.10.10 Recommended BDM Connection	4-26
4.10.11 Deterministic Opcode Tracking	4-26
4.10.12 On-Chip Breakpoint Hardware	4-27



**Section 5
SYSTEM INTEGRATION MODULE**

5.1 General	5-1
5.2 System Configuration	5-2
5.2.1 Module Mapping	5-2
5.2.2 Interrupt Arbitration	5-2
5.2.3 Show Internal Cycles	5-3
5.2.4 Register Access	5-3
5.2.5 Freeze Operation	5-3
5.3 System Clock	5-3
5.3.1 Clock Sources	5-4
5.3.2 Clock Synthesizer Operation	5-5
5.3.3 External Bus Clock	5-10
5.3.4 Low-Power Operation	5-11
5.4 System Protection	5-12
5.4.1 Reset Status	5-13

Paragraph Number	Page Number
5.4.2 Bus Monitor	5-13
5.4.3 Halt Monitor	5-14
5.4.4 Spurious Interrupt Monitor	5-14
5.4.5 Software Watchdog	5-14
5.4.6 Periodic Interrupt Timer	5-16
5.4.7 Interrupt Priority and Vectoring	5-17
5.4.8 Low-Power STOP Mode Operation	5-18
5.5 External Bus Interface	5-18
5.5.1 Bus Control Signals	5-20
5.5.1.1 Address Bus	5-20
5.5.1.2 Address Strobe	5-20
5.5.1.3 Data Bus	5-20
5.5.1.4 Data Strobe	5-20
5.5.1.5 Read/Write Signal	5-21
5.5.1.6 Size Signals	5-21
5.5.1.7 Function Codes	5-21
5.5.1.8 Data and Size Acknowledge Signals	5-22
5.5.1.9 Bus Error Signal	5-22
5.5.1.10 Halt Signal	5-22
5.5.1.11 Autovector Signal	5-22
5.5.2 Dynamic Bus Sizing	5-23
5.5.3 Operand Alignment	5-24
5.5.4 Misaligned Operands	5-24
5.5.5 Operand Transfer Cases	5-24
5.6 Bus Operation	5-25
5.6.1 Synchronization to CLKOUT	5-25
5.6.2 Regular Bus Cycles	5-26
5.6.2.1 Read Cycle	5-27
5.6.2.2 Write Cycle	5-27
5.6.3 Fast Termination Cycles	5-28
5.6.4 CPU Space Cycles	5-29
5.6.4.1 Breakpoint Acknowledge Cycle	5-30
5.6.4.2 LPSTOP Broadcast Cycle	5-33
5.6.5 Bus Exception Control Cycles	5-33
5.6.5.1 Bus Errors	5-35
5.6.5.2 Double Bus Faults	5-35
5.6.5.3 Retry Operation	5-36
5.6.5.4 Halt Operation	5-36
5.6.6 External Bus Arbitration	5-37
5.6.6.1 Show Cycles	5-38
5.7 Reset	5-39
5.7.1 Reset Exception Processing	5-39
5.7.2 Reset Control Logic	5-39



Paragraph Number	Page Number
5.7.3 Reset Mode Selection	5-40
5.7.3.1 Data Bus Mode Selection.....	5-41
5.7.3.2 Clock Mode Selection.....	5-43
5.7.3.3 Breakpoint Mode Selection.....	5-44
5.7.4 MCU Module Pin Function During Reset	5-44
5.7.5 Pin States During Reset	5-45
5.7.5.1 Reset States of SIM Pins	5-45
5.7.5.2 Reset States of Pins Assigned to Other MCU Modules	5-46
5.7.6 Reset Timing	5-46
5.7.7 Power-On Reset.....	5-47
5.7.8 Use of the Three-State Control Pin	5-48
5.7.9 Reset Processing Summary.....	5-48
5.7.10 Reset Status Register.....	5-49
5.8 Interrupts	5-49
5.8.1 Interrupt Exception Processing.....	5-49
5.8.2 Interrupt Priority and Recognition.....	5-50
5.8.3 Interrupt Acknowledge and Arbitration	5-51
5.8.4 Interrupt Processing Summary.....	5-52
5.8.5 Interrupt Acknowledge Bus Cycles.....	5-53
5.9 Chip-Selects.....	5-53
5.9.1 Chip-Select Registers.....	5-55
5.9.1.1 Chip-Select Pin Assignment Registers.....	5-56
5.9.1.2 Chip-Select Base Address Registers	5-57
5.9.1.3 Chip-Select Option Registers.....	5-58
5.9.1.4 Port C Data Register	5-59
5.9.2 Chip-Select Operation	5-59
5.9.3 Using Chip-Select Signals for Interrupt Acknowledge	5-60
5.9.4 Chip-Select Reset Operation	5-61
5.10 Parallel Input/Output Ports.....	5-63
5.10.1 Pin Assignment Registers	5-63
5.10.2 Data Direction Registers.....	5-63
5.10.3 Data Registers	5-63
5.11 Factory Test	5-64



**Section 6
STANDBY RAM MODULE**

6.1 SRAM Register Block.....	6-1
6.2 SRAM Array Address Mapping	6-1
6.3 SRAM Array Address Space Type.....	6-1
6.4 Normal Access.....	6-2
6.5 Standby and Low-Power Stop Operation.....	6-2
6.6 Reset	6-3



**Section 7
MASKED ROM MODULE**

7.1 MRM Register Block	7-1
7.2 MRM Array Address Mapping	7-1
7.3 MRM Array Address Space Type.....	7-2
7.4 Normal Access	7-2
7.5 Low-Power Stop Mode Operation	7-3
7.6 ROM Signature	7-3
7.7 Reset	7-3

**Section 8
QUEUED ANALOG-TO-DIGITAL CONVERTER MODULE**

8.1 General	8-1
8.2 QADC Address Map.....	8-2
8.3 QADC Registers.....	8-2
8.4 QADC Pin Functions	8-2
8.4.1 Port A Pin Functions.....	8-3
8.4.1.1 Port A Analog Input Pins	8-3
8.4.1.2 Port A Digital Input/Output Pins	8-4
8.4.2 Port B Pin Functions.....	8-4
8.4.2.1 Port B Analog Input Pins	8-4
8.4.2.2 Port B Digital Input Pins	8-4
8.4.3 External Trigger Input Pins.....	8-4
8.4.4 Multiplexed Address Output Pins	8-5
8.4.5 Multiplexed Analog Input Pins	8-5
8.4.6 Voltage Reference Pins	8-5
8.4.7 Dedicated Analog Supply Pins	8-5
8.4.8 External Digital Supply Pin	8-6
8.4.9 Digital Supply Pins	8-6
8.5 QADC Bus Interface.....	8-6
8.6 Module Configuration.....	8-6
8.6.1 Low-Power Stop Mode	8-6
8.6.2 Freeze Mode	8-7
8.6.3 Supervisor/Unrestricted Address Space.....	8-7
8.6.4 Interrupt Arbitration Priority.....	8-8
8.7 Test Register	8-8
8.8 General-Purpose I/O Port Operation	8-8
8.8.1 Port Data Register	8-9
8.8.2 Port Data Direction Register.....	8-9
8.9 External Multiplexing Operation	8-9
8.10 Analog Input Channels.....	8-11
8.11 Analog Subsystem	8-12
8.11.1 Conversion Cycle Times.....	8-13

Paragraph Number	Page Number
8.11.1.1 Amplifier Bypass Mode Conversion Timing	8-14
8.11.2 Front-End Analog Multiplexer	8-15
8.11.3 Digital to Analog Converter Array	8-15
8.11.4 Comparator	8-15
8.11.5 Successive Approximation Register	8-16
8.12 Digital Control Subsystem	8-16
8.12.1 Queue Priority	8-16
8.12.2 Queue Boundary Conditions	8-19
8.12.3 Scan Modes	8-20
8.12.3.1 Disabled Mode and Reserved Mode	8-20
8.12.3.2 Single-Scan Modes	8-20
8.12.3.3 Continuous-Scan Modes	8-21
8.12.4 QADC Clock (QCLK) Generation	8-23
8.12.5 Periodic/Interval Timer	8-27
8.12.6 Control and Status Registers	8-27
8.12.6.1 Control Register 0 (QACR0)	8-27
8.12.6.2 Control Register 1 (QACR1)	8-28
8.12.6.3 Control Register 2 (QACR2)	8-28
8.12.6.4 Status Register (QASR)	8-28
8.12.7 Conversion Command Word Table	8-28
8.12.8 Result Word Table	8-31
8.13 Interrupts	8-31
8.13.1 Interrupt Sources	8-31
8.13.2 Interrupt Register	8-32
8.13.3 Interrupt Vectors	8-32
8.13.4 Initializing the QADC for Interrupt Driven Operation	8-33



Section 9 QUEUED SERIAL MODULE

9.1 General	9-1
9.2 QSM Registers and Address Map	9-2
9.2.1 QSM Global Registers	9-2
9.2.1.1 Low-Power Stop Operation	9-2
9.2.1.2 Freeze Operation	9-3
9.2.1.3 QSM Interrupts	9-3
9.2.2 QSM Pin Control Registers	9-4
9.3 Queued Serial Peripheral Interface	9-5
9.3.1 QSPI Registers	9-7
9.3.1.1 Control Registers	9-7
9.3.1.2 Status Register	9-8
9.3.2 QSPI RAM	9-8
9.3.2.1 Receive RAM	9-8
9.3.2.2 Transmit RAM	9-8

Paragraph Number	Page Number
9.3.2.3 Command RAM	9-9
9.3.3 QSPI Pins	9-9
9.3.4 QSPI Operation	9-9
9.3.5 QSPI Operating Modes	9-10
9.3.5.1 Master Mode	9-17
9.3.5.2 Master Wrap-Around Mode	9-20
9.3.5.3 Slave Mode	9-20
9.3.5.4 Slave Wrap-Around Mode	9-22
9.3.6 Peripheral Chip Selects	9-22
9.4 Serial Communication Interface	9-22
9.4.1 SCI Registers	9-22
9.4.1.1 Control Registers	9-23
9.4.1.2 Status Register	9-26
9.4.1.3 Data Register	9-26
9.4.2 SCI Pins	9-26
9.4.3 SCI Operation	9-26
9.4.3.1 Definition of Terms	9-26
9.4.3.2 Serial Formats	9-27
9.4.3.3 Baud Clock	9-27
9.4.3.4 Parity Checking	9-28
9.4.3.5 Transmitter Operation	9-28
9.4.3.6 Receiver Operation	9-30
9.4.3.7 Idle-Line Detection	9-30
9.4.3.8 Receiver Wake-Up	9-31
9.4.3.9 Internal Loop	9-32
9.5 QSM Initialization	9-32



Section 10
CONFIGURABLE TIMER MODULE 4

10.1 General	10-1
10.2 Address Map	10-2
10.3 Time Base Bus System	10-2
10.4 Bus Interface Unit Submodule (BIUSM)	10-3
10.4.1 STOP Effect On the BIUSM	10-3
10.4.2 Freeze Effect On the BIUSM	10-3
10.4.3 LPSTOP Effect on the BIUSM	10-4
10.4.4 BIUSM Registers	10-4
10.5 Counter Prescaler Submodule (CPSM)	10-4
10.5.1 CPSM Registers	10-5
10.6 Free-Running Counter Submodule (FCSM)	10-5
10.6.1 FCSM Counter	10-6
10.6.2 FCSM Clock Sources	10-6
10.6.3 FCSM External Event Counting	10-7

Paragraph Number	Page Number
10.6.4 FCSM Time Base Bus Driver	10-7
10.6.5 FCSM Interrupts	10-7
10.6.6 FCSM Registers	10-7
10.7 Modulus Counter Submodule (MCSM)	10-7
10.7.1 MCSM Modulus Latch	10-8
10.7.2 MCSM Counter	10-8
10.7.2.1 Loading the MCSM Counter Register	10-9
10.7.2.2 Using the MCSM as a Free-Running Counter	10-9
10.7.3 MCSM Clock Sources	10-9
10.7.4 MCSM External Event Counting	10-9
10.7.5 MCSM Time Base Bus Driver	10-9
10.7.6 MCSM Interrupts	10-9
10.7.7 MCSM Registers	10-10
10.8 Double-Action Submodule (DASM)	10-10
10.8.1 DASM Interrupts	10-12
10.8.2 DASM Registers	10-12
10.9 Pulse-Width Modulation Submodule (PWMSM)	10-13
10.9.1 Output Flip-Flop and Pin	10-14
10.9.2 Clock Selection	10-14
10.9.3 PWMSM Counter	10-15
10.9.4 PWMSM Period Registers and Comparator	10-15
10.9.5 PWMSM Pulse-Width Registers and Comparator	10-16
10.9.6 PWMSM Coherency	10-16
10.9.7 PWMSM Interrupts	10-16
10.9.8 PWM Frequency	10-17
10.9.9 PWM Pulse Width	10-18
10.9.10 PWM Period and Pulse Width Register Values	10-18
10.9.10.1 PWM Duty Cycle Boundary Cases	10-18
10.9.11 PWMSM Registers	10-19
10.10 CTM4 Interrupts	10-19



Section 11 TIME PROCESSOR UNIT

11.1 General	11-1
11.2 TPU Components	11-2
11.2.1 Time Bases	11-2
11.2.2 Timer Channels	11-2
11.2.3 Scheduler	11-3
11.2.4 Microengine	11-3
11.2.5 Host Interface	11-3
11.2.6 Parameter RAM	11-3
11.3 TPU Operation	11-3
11.3.1 Event Timing	11-4

Paragraph Number	Page Number
11.3.2 Channel Orthogonality	11-4
11.3.3 Interchannel Communication	11-4
11.3.4 Programmable Channel Service Priority	11-4
11.3.5 Coherency	11-4
11.3.6 Emulation Support	11-5
11.3.7 TPU Interrupts	11-5
11.4 A Mask Set Time Functions	11-6
11.4.1 Discrete Input/Output (DIO)	11-6
11.4.2 Input Capture/Input Transition Counter (ITC)	11-6
11.4.3 Output Compare (OC)	11-7
11.4.4 Pulse-Width Modulation (PWM)	11-7
11.4.5 Synchronized Pulse-Width Modulation (SPWM)	11-7
11.4.6 Period Measurement with Additional Transition Detect (PMA)	11-7
11.4.7 Period Measurement with Missing Transition Detect (PMM)	11-8
11.4.8 Position-Synchronized Pulse Generator (PSP)	11-8
11.4.9 Stepper Motor (SM)	11-9
11.4.10 Period/Pulse-Width Accumulator (PPWA)	11-9
11.4.11 Quadrature Decode (QDEC)	11-10
11.5 G Mask Set Time Functions	11-10
11.5.1 Table Stepper Motor (TSM)	11-10
11.5.2 New Input Capture/Transition Counter (NITC)	11-11
11.5.3 Queued Output Match (QOM)	11-11
11.5.4 Programmable Time Accumulator (PTA)	11-11
11.5.5 Multichannel Pulse-Width Modulation (MCPWM)	11-11
11.5.6 Fast Quadrature Decode (FQD)	11-12
11.5.7 Universal Asynchronous Receiver/Transmitter (UART)	11-12
11.5.8 Brushless Motor Commutation (COMM)	11-12
11.5.9 Frequency Measurement (FQM)	11-12
11.5.10 Hall Effect Decode (HALLD)	11-13
11.6 Host Interface Registers	11-13
11.6.1 System Configuration Registers	11-13
11.6.1.1 Prescaler Control for TCR1	11-13
11.6.1.2 Prescaler Control for TCR2	11-14
11.6.1.3 Emulation Control	11-15
11.6.1.4 Low-Power Stop Control	11-15
11.6.2 Channel Control Registers	11-15
11.6.2.1 Channel Interrupt Enable and Status Registers	11-15
11.6.2.2 Channel Function Select Registers	11-16
11.6.2.3 Host Sequence Registers	11-16
11.6.2.4 Host Service Registers	11-16
11.6.2.5 Channel Priority Registers	11-17
11.6.3 Development Support and Test Registers	11-17





**Section 12
STANDBY RAM WITH TPU EMULATION**

12.1	General	12-1
12.2	TPURAM Register Block	12-1
12.3	TPURAM Array Address Mapping	12-1
12.4	TPURAM Privilege Level	12-2
12.5	Normal Operation	12-2
12.6	Standby Operation	12-2
12.7	Low-Power Stop Operation	12-3
12.8	Reset	12-3
12.9	TPU Microcode Emulation	12-3

**Section 13
CAN 2.0B CONTROLLER MODULE (TouCAN)**

13.1	General	13-1
13.2	External Pins	13-2
13.3	Programmer's Model	13-2
13.4	TouCAN Architecture	13-3
13.4.1	TX/RX Message Buffer Structure	13-3
13.4.1.1	Common Fields for Extended and Standard Format Frames	13-4
13.4.1.2	Fields for Extended Format Frames	13-5
13.4.1.3	Fields for Standard Format Frames	13-6
13.4.1.4	Serial Message Buffers	13-6
13.4.1.5	Message Buffer Activation/Deactivation Mechanism	13-6
13.4.1.6	Message Buffer Lock/Release/Busy Mechanism	13-7
13.4.2	Receive Mask Registers	13-7
13.4.3	Bit Timing	13-8
13.4.3.1	Configuring the TouCAN Bit Timing	13-9
13.4.4	Error Counters	13-9
13.4.5	Time Stamp	13-10
13.5	TouCAN Operation	13-11
13.5.1	TouCAN Reset	13-11
13.5.2	TouCAN Initialization	13-11
13.5.3	Transmit Process	13-12
13.5.3.1	Transmit Message Buffer Deactivation	13-13
13.5.3.2	Reception of Transmitted Frames	13-13
13.5.4	Receive Process	13-13
13.5.4.1	Receive Message Buffer Deactivation	13-14
13.5.4.2	Locking and Releasing Message Buffers	13-14
13.5.5	Remote Frames	13-15
13.5.6	Overload Frames	13-16
13.6	Special Operating Modes	13-16
13.6.1	Debug Mode	13-16

**Paragraph
Number**

**Page
Number**



13.6.2	Low-Power Stop Mode	13-17
13.6.3	Auto Power Save Mode	13-18
13.7	Interrupts	13-18

**Appendix A
ELECTRICAL CHARACTERISTICS**

**Appendix B
MECHANICAL DATA AND ORDERING INFORMATION**

**Appendix C
DEVELOPMENT SUPPORT**

C.1	M68MMDS1632 Modular Development System	C-1
C.2	M68MEVB1632 Modular Evaluation Board	C-1

**Appendix D
REGISTER SUMMARY**

D.1	Central Processor Unit	D-1
D.1.1	CPU32 Register Model	D-2
D.1.2	Status Register	D-3
D.2	System Integration Module	D-4
D.2.1	SIM Configuration Register	D-6
D.2.2	System Integration Test Register	D-7
D.2.3	Clock Synthesizer Control Register	D-7
D.2.4	Reset Status Register	D-8
D.2.5	System Integration Test Register (ECLK)	D-9
D.2.6	Port E Data Register	D-9
D.2.7	Port E Data Direction Register	D-9
D.2.8	Port E Pin Assignment Register	D-10
D.2.9	Port F Data Register	D-10
D.2.10	Port F Data Direction Register	D-11
D.2.11	Port F Pin Assignment Register	D-11
D.2.12	System Protection Control Register	D-12
D.2.13	Periodic Interrupt Control Register	D-13
D.2.14	Periodic Interrupt Timer Register	D-13
D.2.15	Software Watchdog Service Register	D-14
D.2.16	Port C Data Register	D-14
D.2.17	Chip-Select Pin Assignment Registers	D-15
D.2.18	Chip-Select Base Address Register Boot ROM	D-17
D.2.19	Chip-Select Base Address Registers	D-17
D.2.20	Chip-Select Option Register Boot ROM	D-18
D.2.21	Chip-Select Option Registers	D-18
D.2.22	Master Shift Registers	D-20
D.2.23	Test Module Shift Count Register	D-21
D.2.24	Test Module Repetition Count Register	D-21
D.2.25	Test Submodule Control Register	D-21
D.2.26	Distributed Register	D-21
D.3	Standby RAM Module	D-21
D.3.1	RAM Module Configuration Register	D-21
D.3.2	RAM Test Register	D-22
D.3.3	Array Base Address Register High	D-22
D.3.4	Array Base Address Register Low	D-22

Paragraph Number	Page Number
D.4 Masked ROM Module	D-23
D.4.1 Masked ROM Module Configuration Register	D-23
D.4.2 ROM Array Base Address Register High	D-25
D.4.3 ROM Array Base Address Register Low	D-25
D.4.4 ROM Signature High Register	D-25
D.4.5 ROM Signature Low Register	D-26
D.4.6 ROM Bootstrap Words	D-26
D.5 QADC Module	D-26
D.5.1 QADC Module Configuration Register	D-27
D.5.2 QADC Test Register	D-28
D.5.3 QADC Interrupt Register	D-28
D.5.4 Port A/B Data Register	D-29
D.5.5 Port Data Direction Register	D-29
D.5.6 QADC Control Registers	D-30
D.5.7 QADC Status Register	D-34
D.5.8 Conversion Command Word Table	D-36
D.5.9 Result Word Table	D-38
D.6 Queued Serial Module	D-39
D.6.1 QSM Configuration Register	D-40
D.6.2 QSM Test Register	D-40
D.6.3 QSM Interrupt Level Register	D-41
D.6.4 QSM Interrupt Vector Register	D-41
D.6.5 SCI Control Register	D-42
D.6.7 SCI Status Register	D-44
D.6.8 SCI Data Register	D-45
D.6.9 Port QS Data Register	D-45
D.6.10 Port QS Pin Assignment Register/Data Direction Register	D-46
D.6.11 QSPI Control Register 0	D-47
D.6.12 QSPI Control Register 1	D-49
D.6.13 QSPI Control Register 2	D-50
D.6.14 QSPI Control Register 3	D-51
D.6.15 QSPI Status Register	D-52
D.6.16 Receive Data RAM	D-52
D.6.17 Transmit Data RAM	D-53
D.6.18 Command RAM	D-53
D.7 Configurable Timer Module 4	D-54
D.7.1 BIU Module Configuration Register	D-55
D.7.2 BIUSM Test Configuration Register	D-56
D.7.3 BIUSM Time Base Register	D-56
D.7.4 CPSM Control Register	D-57
D.7.5 CPSM Test Register	D-57
D.7.6 FCSM Status/Interrupt/Control Register	D-58
D.7.7 FCSM Counter Register	D-59
D.7.8 MCSM Status/Interrupt/Control Registers	D-59
D.7.9 MCSM Counter Registers	D-61
D.7.10 MCSM Modulus Latch Registers	D-61
D.7.11 DASM Status/Interrupt/Control Registers	D-62
D.7.12 DASM Data Register A	D-65
D.7.13 DASM Data Register B	D-65
D.7.14 PWM Status/Interrupt/Control Register	D-66
D.7.15 PWM Period Register	D-69
D.7.16 PWM Pulse Width Register	D-69
D.7.17 PWM Counter Register	D-70
D.8 Time Processor Unit (TPU)	D-70



**Paragraph
Number**

**Page
Number**



D.8.1	TPU Module Configuration Register	D-71
D.8.2	Test Configuration Register	D-73
D.8.3	Development Support Control Register	D-73
D.8.4	Development Support Status Register.	D-74
D.8.5	TPU Interrupt Configuration Register.	D-75
D.8.6	Channel Interrupt Enable Register.	D-75
D.8.7	Channel Function Select Registers	D-75
D.8.8	Host Sequence Registers	D-76
D.8.9	Host Service Request Registers	D-77
D.8.10	Channel Priority Registers	D-77
D.8.11	Channel Interrupt Status Register	D-78
D.8.12	Link Register	D-78
D.8.13	Service Grant Latch Register	D-78
D.8.14	Decoded Channel Number Register	D-78
D.8.15	TPU Parameter RAM	D-78
D.9	Standby RAM Module with TPU Emulation Capability (TPURAM)	D-79
D.9.1	TPURAM Module Configuration Register	D-80
D.9.2	TPURAM Test Register	D-80
D.9.3	TPURAM Module Configuration Register	D-80
D.10	TouCAN Module	D-80
D.10.1	TouCAN Module Configuration Register	D-82
D.10.2	TouCAN Test Configuration Register	D-85
D.10.3	TouCAN Interrupt Configuration Register	D-85
D.10.4	Control Register 0	D-85
D.10.5	Control Register 1	D-87
D.10.6	Prescaler Divide Register	D-88
D.10.7	Control Register 2	D-88
D.10.8	Free Running Timer	D-89
D.10.9	Receive Global Mask Registers	D-90
D.10.10	Receive Buffer 14 Mask Registers.	D-90
D.10.11	Receive Buffer 15 Mask Registers.	D-90
D.10.12	Error and Status Register	D-91
D.10.13	Interrupt Mask Register	D-93
D.10.14	Interrupt Flag Register	D-93
D.10.15	Error Counters	D-94

INDEX

Online publishing by JABIS™, <http://www.jabis.com>

