



By Martin Niset and Peter Kuhn
NVM Reliability
Austin, Texas

Introduction

This document explains how Motorola defines typical endurance in the product specification of nonvolatile memory (NVM).

Definition

Endurance refers to the ability of a memory bit to withstand the repeated operation of program/erase (P/E) events and still meet the performance for program and erase time.

Motorola guarantees a minimum endurance in its product specification. In practice, the technology is capable of producing much greater endurance than the specified minimum. To give a better representation of the endurance that can be achieved under nominal conditions¹, Motorola also provides a typical value in the product specification.

Motorola defines typical endurance as the number of P/E cycles that most parts can achieve without failure. It is evaluated by stressing an industry standard sample size^{2,3} at room temperature until intrinsic wear out is observed or until extensive margin to the endurance specification has been achieved.

Example

- Cycle to 500 k. Failures starting @ 356 k → Typical Endurance > 350 k
- Cycle to 500 k. No fail @ 500 k → Typical Endurance > 500 k

1. Nominal conditions = room temperature, nominal supply voltage, nominal program and erase time

2. Typically, 3 lots, 77 units per lot

3. Generally, the typical endurance evaluation is performed on a single product of the family.

Typical Endurance for Motorola NVM Technologies

Using the above definition, the following NVM technologies from Motorola are capable of achieving significant margin to the minimum specified number of W/E cycles.

Table 1. Typical Endurance for Motorola NVM Technologies

Technology	Specification		Typical Number of Cycles at 25°C
	Number of Cycles	Temperature (°C)	
CDR1	100	-40 to 125	Not Characterized
CDR3	1 k	-40 to 125	>100 k
0.5µm SGF FLASH	10 k	-40 to 125	>100 k
0.5µm SGF EEPROM	10 k	-40 to 125	>100 k ⁽¹⁾
0.25µm SGF FLASH	10 k	-40 to 125	>100 k ⁽²⁾
0.25µm SGF EEPROM	10 k	-40 to 0	>300 k ⁽²⁾
	100 k	0 to 125	

1. EEPROM typical endurance value is based on the FLASH characterization
2. The following HCS12 devices use an earlier generation of the FLASH and are not covered by this engineering bulletin: MC9S12DT256B, MC9S12DJ256B, MC9S12A256B, MC9S12DG128B, MC9S12DJ128B, MC9S12DT128B, MC9S12A128B. These devices have, or will be, upgraded to current FLASH technology that is covered here and then will be available as MC9S12DT256, MC9S12DJ256, MC9S12A256, MC9S12DG128, MC9S12DJ128, MC9S12DT128, and MC9S12A128. Other devices using the earlier generation of the FLASH and not covered by this engineering bulletin are: MMC2114CFCVF33, MMC2114CFCPU33, MMC2114CFCPU33, MMC2113CFCVF33, MMC2113CFCPU33, MMC2113CFCPU33, DSP56F801, DSP56F802, DSP56F803, DSP56F805, DSP56F807, DSP56F826, and DSP56F827.

HOW TO REACH US:

USA/EUROPE/LOCATIONS NOT LISTED:

Motorola Literature Distribution
P.O. Box 5405
Denver, Colorado 80217
1-800-521-6274 or 480-768-2130

JAPAN:

Motorola Japan Ltd.
SPS, Technical Information Center
3-20-1, Minami-Azabu, Minato-ku
Tokyo 106-8573, Japan
81-3-3440-3569

ASIA/PACIFIC:

Motorola Semiconductors H.K. Ltd.
Silicon Harbour Centre
2 Dai King Street
Tai Po Industrial Estate
Tai Po, N.T., Hong Kong
852-26668334

HOME PAGE:

<http://motorola.com/semiconductors>

Information in this document is provided solely to enable system and software implementers to use Motorola products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part.



Motorola and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. digital dna is a trademark of Motorola, Inc. All other product or service names are the property of their respective owners. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

© Motorola, Inc. 2003

EB619/D

**For More Information On This Product,
Go to: www.freescale.com**